



US008695888B2

(12) **United States Patent**
Kates

(10) **Patent No.:** **US 8,695,888 B2**
(45) **Date of Patent:** **Apr. 15, 2014**

(54) **ELECTRONICALLY-CONTROLLED REGISTER VENT FOR ZONE HEATING AND COOLING**

(75) Inventor: **Lawrence Kates**, Corona del Mar, CA (US)

(73) Assignee: **Nest Labs, Inc.**, Palo Alto, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 219 days.

(21) Appl. No.: **13/269,155**

(22) Filed: **Oct. 7, 2011**

(65) **Prior Publication Data**

US 2012/0024969 A1 Feb. 2, 2012

Related U.S. Application Data

(63) Continuation of application No. 11/669,066, filed on Jan. 30, 2007, now Pat. No. 8,033,479, which is a continuation-in-part of application No. 10/959,362, filed on Oct. 6, 2004, now Pat. No. 7,168,627.

(51) **Int. Cl.**
F24F 7/00 (2006.01)

(52) **U.S. Cl.**
USPC **236/49.3**; 62/186; 62/296

(58) **Field of Classification Search**
USPC 236/49.3; 62/186, 296, 404; 454/256, 454/284

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,640,455 A * 2/1972 Romanelli 236/49.3
3,724,534 A 4/1973 Weatherston
4,183,290 A * 1/1980 Kucharczyk 454/256
4,330,047 A 5/1982 Ruspa et al.

4,417,687 A 11/1983 Grant
4,646,964 A 3/1987 Parker et al.
4,656,835 A 4/1987 Kidder et al.
4,657,179 A 4/1987 Aggers et al.
4,716,957 A 1/1988 Thompson et al.
4,742,475 A 5/1988 Kaiser et al.
4,754,697 A 7/1988 Asselbergs
4,809,593 A 3/1989 Asselbergs

(Continued)

FOREIGN PATENT DOCUMENTS

BE 1001873 4/1990
CA 1187966 5/1985

(Continued)

OTHER PUBLICATIONS

6 Zone HVAC Control Unit, Residential Control Systems, Inc. (RCS) Product Specification Model ZC6R, Feb. 2002, 2 pages.

(Continued)


Primary Examiner — Marc Norman

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

(57) **ABSTRACT**

An Electronically-Controlled Register vent (ECRV) that can be easily installed by a homeowner or general handyman is disclosed. The ECRV can be used to convert a non-zoned HVAC system into a zoned system. The ECRV can also be used in connection with a conventional zoned HVAC system to provide additional control and additional zones not provided by the conventional zoned HVAC system. In one embodiment, the ECRV is configured have a size and form-factor that conforms to a standard manually-controlled register vent. In one embodiment, a zone thermostat is configured to provide thermostat information to the ECRV. In one embodiment, the zone thermostat communicates with a central monitoring system that coordinates operation of the heating and cooling zones.

20 Claims, 20 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,824,012 A	4/1989	Tate	7,163,156 B2	1/2007	Kates
4,830,095 A	5/1989	Friend	7,167,079 B2	1/2007	Smyth et al.
RE32,960 E	6/1989	Levine	7,168,627 B2	1/2007	Kates
4,846,399 A	7/1989	Asselbergs	7,181,317 B2	2/2007	Amundson et al.
4,886,110 A	12/1989	Jackson	7,289,887 B2	10/2007	Rodgers
4,942,348 A	7/1990	Nilssen	7,360,370 B2	4/2008	Shah et al.
4,948,040 A	8/1990	Kobayashi et al.	RE40,437 E	7/2008	Rosen
D310,873 S	9/1990	Asselbergs	7,434,742 B2	10/2008	Mueller et al.
5,065,813 A	11/1991	Berkeley et al.	7,455,236 B2	11/2008	Kates
5,161,606 A	11/1992	Berkeley et al.	7,455,237 B2	11/2008	Kates
5,224,648 A	7/1993	Simon et al.	7,460,690 B2	12/2008	Cohen et al.
5,271,558 A	12/1993	Hampton	7,469,550 B2	12/2008	Chapman, Jr. et al.
5,301,101 A	4/1994	MacArthur et al.	7,537,171 B2	5/2009	Mueller et al.
5,303,767 A	4/1994	Riley	7,558,648 B2	7/2009	Hoglund et al.
5,318,104 A	6/1994	Shah et al.	7,562,536 B2	7/2009	Harrod et al.
5,348,078 A	9/1994	Dushane et al.	7,571,865 B2	8/2009	Nicodem et al.
5,364,304 A	11/1994	Hampton	7,605,714 B2	10/2009	Thompson et al.
5,381,950 A	1/1995	Aldridge	7,634,504 B2	12/2009	Amundson
5,395,042 A	3/1995	Riley et al.	7,703,694 B2	4/2010	Mueller et al.
5,449,319 A	9/1995	Dushane et al.	D614,976 S	5/2010	Skafdrup et al.
5,452,762 A	9/1995	Zillner, Jr.	7,748,640 B2	7/2010	Roher et al.
5,467,921 A	11/1995	Shreeve et al.	7,832,465 B2	11/2010	Zou et al.
5,489,238 A	2/1996	Asselbergs	7,837,128 B2	11/2010	Helt et al.
5,495,887 A	3/1996	Kathnelson et al.	7,844,764 B2	11/2010	Williams
5,533,668 A	7/1996	Erikson	7,847,681 B2	12/2010	Singhal et al.
5,544,036 A	8/1996	Brown, Jr. et al.	7,904,209 B2	3/2011	Podgorny et al.
5,595,342 A	1/1997	McNair et al.	7,904,830 B2	3/2011	Hoglund et al.
5,611,484 A	3/1997	Uhrich	8,033,479 B2 *	10/2011	Kates 236/1 B
5,622,221 A	4/1997	Genga, Jr. et al.	8,037,022 B2	10/2011	Rahman et al.
5,635,896 A	6/1997	Tinsley et al.	8,067,912 B2	11/2011	Mullin
5,644,173 A	7/1997	Elliason et al.	2001/0048030 A1	12/2001	Sharood et al.
5,711,480 A	1/1998	Zepke et al.	2002/0017107 A1	2/2002	Bailey et al.
5,761,083 A	6/1998	Brown, Jr. et al.	2003/0231001 A1	12/2003	Bruning
5,802,467 A	9/1998	Salazar et al.	2004/0130454 A1	7/2004	Barton
5,810,245 A	9/1998	Heitman et al.	2004/0193324 A1	9/2004	Hoog et al.
5,819,840 A	10/1998	Wilson et al.	2004/0194484 A1	10/2004	Zou et al.
5,839,654 A	11/1998	Weber	2004/0211200 A1	10/2004	McMillan et al.
5,926,776 A	7/1999	Glorioso et al.	2004/0224627 A1	11/2004	Becelaere et al.
5,944,098 A	8/1999	Jackson	2004/0238651 A1	12/2004	Juntunen et al.
5,950,709 A	9/1999	Krueger et al.	2005/0040250 A1	2/2005	Wruck
6,023,938 A	2/2000	Taras et al.	2005/0043907 A1	2/2005	Eckel et al.
6,102,749 A	8/2000	Lynn et al.	2005/0082053 A1	4/2005	Halabi
6,116,512 A	9/2000	Dushane et al.	2005/0156731 A1	7/2005	Chapman et al.
6,145,752 A	11/2000	Jackson	2005/0159846 A1	7/2005	Van Ostrand et al.
6,250,382 B1	6/2001	Rayburn et al.	2005/0194455 A1	9/2005	Alles
6,322,443 B1	11/2001	Jackson	2005/0194456 A1	9/2005	Tessier et al.
6,338,677 B1	1/2002	White	2005/0270151 A1	12/2005	Winick
6,385,510 B1	5/2002	Hoog et al.	2005/0284622 A1	12/2005	Nichols
6,453,687 B2	9/2002	Sharood et al.	2006/0071086 A1	4/2006	Kates
6,488,081 B2	12/2002	Rayburn et al.	2006/0071087 A1	4/2006	Kates
6,491,094 B2	12/2002	Rayburn et al.	2006/0071089 A1	4/2006	Kates
6,519,509 B1	2/2003	Nierlich et al.	2006/0105697 A1	5/2006	Aronstam et al.
6,574,581 B1	6/2003	Bohrer et al.	2006/0149395 A1	7/2006	Archacki et al.
6,604,023 B1	8/2003	Brown et al.	2006/0186214 A1	8/2006	Simon et al.
6,619,055 B1	9/2003	Addy	2006/0208099 A1	9/2006	Chapman et al.
6,619,555 B2	9/2003	Rosen	2007/0037507 A1	2/2007	Liu
6,622,115 B1	9/2003	Brown et al.	2007/0045441 A1	3/2007	Ashworth et al.
6,622,925 B2	9/2003	Carner et al.	2007/0082601 A1	4/2007	Desrochers et al.
6,692,349 B1	2/2004	Brinkerhoff et al.	2007/0095518 A1	5/2007	Kates
6,798,341 B1	9/2004	Eckel et al.	2007/0102149 A1	5/2007	Kates
6,851,621 B1	2/2005	Wacker et al.	2007/0114295 A1	5/2007	Jenkins
6,851,967 B2	2/2005	Miyoshi et al.	2007/0115902 A1	5/2007	Shamoon et al.
6,891,838 B1	5/2005	Petite et al.	2007/0119957 A1	5/2007	Kates
6,909,921 B1	6/2005	Bilger	2007/0131787 A1	6/2007	Rossi et al.
6,912,429 B1	6/2005	Bilger	2007/0157639 A1	7/2007	Harrod
6,975,958 B2	12/2005	Bohrer et al.	2007/0208461 A1	9/2007	Chase
6,983,889 B2	1/2006	Alles	2007/0221741 A1	9/2007	Wagner et al.
6,997,390 B2	2/2006	Alles	2007/0228183 A1	10/2007	Kennedy et al.
7,014,124 B2	3/2006	Gottlieb	2008/0015740 A1	1/2008	Osann
7,055,759 B2	6/2006	Wacker et al.	2008/0015742 A1	1/2008	Kulyk et al.
7,057,506 B2	6/2006	Bash et al.	2008/0099568 A1	5/2008	Nicodem et al.
7,083,109 B2	8/2006	Pouchak	2008/0128523 A1	6/2008	Hoglund et al.
7,135,965 B2	11/2006	Chapman, Jr. et al.	2008/0161977 A1	7/2008	Takach et al.
7,156,316 B2	1/2007	Kates	2008/0179052 A1	7/2008	Kates
7,156,318 B1	1/2007	Rosen	2008/0179053 A1	7/2008	Kates
			2008/0185450 A1	8/2008	Kwon et al.
			2009/0045263 A1	2/2009	Mueller et al.
			2009/0057425 A1	3/2009	Sullivan et al.
			2009/0065595 A1	3/2009	Kates

(56)

References Cited**U.S. PATENT DOCUMENTS**

2009/0140056	A1	6/2009	Leen
2009/0140064	A1	6/2009	Schultz et al.
2009/0140065	A1	6/2009	Juntunen et al.
2009/0143879	A1	6/2009	Amundson et al.
2009/0143880	A1	6/2009	Amundson et al.
2009/0194601	A1	8/2009	Flohr
2009/0236433	A1	9/2009	Mueller et al.
2009/0243842	A1	10/2009	Mitchell et al.
2009/0261174	A1	10/2009	Butler et al.
2010/0000239	A1	1/2010	Lifson et al.
2010/0006660	A1	1/2010	Leen et al.
2010/0012737	A1	1/2010	Kates
2010/0114382	A1	5/2010	Ha et al.
2010/0131112	A1	5/2010	Amundson et al.
2010/0163633	A1	7/2010	Barrett et al.
2010/0163635	A1	7/2010	Ye
2010/0168924	A1	7/2010	Tessier et al.
2010/0250009	A1	9/2010	Lifson et al.
2010/0261465	A1	10/2010	Rhoads et al.
2010/0298985	A1	11/2010	Hess et al.
2010/0305771	A1	12/2010	Rodgers
2011/0001812	A1	1/2011	Kang et al.
2011/0054699	A1	3/2011	Imes et al.
2011/0151837	A1	6/2011	Winbush, III
2011/0253796	A1	10/2011	Posa et al.
2012/0248211	A1	10/2012	Warren et al.

FOREIGN PATENT DOCUMENTS

EP	447458	9/1991
EP	510807	10/1992
EP	632234	1/1995
EP	697571	2/1996
EP	710804	5/1996
EP	710804	12/1997
EP	1614975	1/2006
EP	1275037	2/2006
FR	2671372	7/1992
JP	09298780	11/1997
JP	10023565	1/1998
SI	20556	10/2001
WO	2005019740	3/2005
WO	2006041599	4/2006
WO	2006041599	9/2006
WO	2007027554	3/2007
WO	2008054938	5/2008
WO	2008094166	8/2008

OTHER PUBLICATIONS

A 6-1 Device: Intelligent Residential Control Introduced by Carrier [online]. Carrier Corporation, Jan. 21, 2004. Retrieved from the Internet: <URL: http://www.global.carrier.com/details/O.CLII_DIV28_ETI8093.00.html>, 2 pages.

Aprilaire Electronic Thermostats Model 8355 User's Manual, Research Products Corporation, Dec. 2000, 16 pages.

Automatically Control Your In-Wall or In-Floor Registers! [online] Smarthome, 2004. Retrieved from the Internet: <URL: <http://www.smarthome.com/3096.html>>, 1 page.

Automation for Your Home, Residential Control Systems, Inc. (RCS) Product Catalog #406, Jun. 2004, 14 pages.

Braeburn 5300 Installer Guide, Braeburn Systems, LLC, Dec. 9, 2009, 10 pages.

Braeburn Model 5200, Braeburn Systems, LLC, Jul. 20, 2011, 11 pages.

Comfort System: Commercial VAV & Zone Control Systems Product Specification, Jackson Systems, LLC, Mar. 2003, 14 pages.

DIY Zoning: Can I Do It?, [online] Vadim Tkachenko, Sep. 2004. [Retrieved on Sep. 23, 2004] Retrieved from the Internet: <URL: <http://diy-zoning.sourceforge.net/Advanced/prerequisites.html>>, 4 pages.

DIY Zoning: Dampers [online] Vadim Tkachenko, Sep. 2004. [Retrieved on Sep. 23, 2004] Retrieved from the Internet: <URL: <http://diy-zoning.sourceforge.net/Advanced/dampers.html>>, 3 pages.

DIY Zoning: Passive Mode, [online] Vadim Tkachenko, Sep. 2004. [Retrieved on Sep. 23, 2004] Retrieved from the Internet: <URL: http://diy-zoning.sourceforge.net/Advanced/passive_mode.html>, 2 pages.

DIY Zoning: Release Notes, [online] Vadim Tkachenko, Sep. 2004. [Retrieved on Sep. 23, 2004] Retrieved from the Internet: <URL: http://diy-zoning.sourceforge.net/Advanced/release_notes.html>, 4 pages.

DIY Zoning: Technical FAQ, [online] Vadim Tkachenko, Sep. 2004. [Retrieved on Sep. 23, 2004] Retrieved from the Internet: <URL: <http://diy-zoning.sourceforge.net/Advanced/faq.html>>, 11 pages.

DIY Zoning: Total Control, [online] Vadim Tkachenko, Sep. 2004. [Retrieved on Sep. 23, 2004] Retrieved from the Internet: <URL: http://diy-zoning.sourceforge.net/Advanced/total_control.html>, 3 pages.

Ecobee Smart Thermostat Installation Manual, Jun. 29, 2011, 20 pages.

Ecobee Smart Thermostat User Manual, May 11, 2010, 20 pages.

Honeywell Installation Guide FocusPRO TH6000 Series, Honeywell International, Inc., Jan. 5, 2012, 24 pages.

Honeywell Operating Manual FocusPRO TH6000 Series, Honeywell International, Inc., Mar. 25, 2011, 80 pages.

Honeywell Prestige IAQ Product Data 2, Honeywell International, Inc., Jan. 12, 2012, 126 pages.

Honeywell Prestige THX9321-9421 Operating Manual, Honeywell International, Inc., Jul. 6, 2011, 120 pages.

Hunter Internet Thermostat Installation Guide, Hunter Fan Co., Aug. 14, 2012, 8 pages.

Indoor: Home Comfort: Fans/Air Conditioning: Blower Booster [online] Improvements Catalog, 2003 [Retrieved on Sep. 30, 2004] Retrieved from the Internet: <URL: <http://www.improvementscatalog.com/product.asp?product=49254zz&dept%5Fid=10100.html>>, 1 page.

Lennox ComfortSense 5000 Owners Guide, Lennox Industries, Inc., Feb. 2008, 32 pages.

Lennox ComfortSense 7000 Owners Guide, Lennox Industries, Inc., May 2009, 15 pages.

Lennox iComfort Manual, Lennox Industries, Inc., Dec. 2010, 20 pages.

Lux PSPU732T Manual, LUX Products Corporation, Jan. 6, 2009, 48 pages.

RobertShaw Product Manual 9620, Maple Chase Company, Jun. 12, 2001, 14 pages.

RobertShaw Product Manual 9825i2, Maple Chase Company, Jul. 17, 2006, 36 pages.

SYSTXCCUIZ01-V Infinity Control Installation Instructions, Carrier Corp, May 31, 2012, 20 pages.

TB-PAC, TB-PHP, Base Series Programmable Thermostats, Carrier Corp, May 14, 2012, 8 pages.

TP-PAC, TP-PHP, TP-NAC, TP-NHP Performance Series AC/HP Thermostat Installation Instructions, Carrier Corp, Sep. 2007, 56 pages.

Trane Communicating Thermostats for Fan Coil, Trane, May 2011, 32 pages.

Trane Communicating Thermostats for Heat Pump Control, Trane, May 2011, 32 pages.

Trane Install XL600 Installation Manual, Trane, Mar. 2006, 16 pages.

Trane XL950 Installation Guide, Trane, Mar. 2011, 20 pages.

Venstar T2900 Manual, Venstar, Inc., Apr. 2008, 113 pages.

Venstar T5800 Manual, Venstar, Inc., Sep. 7, 2011, 63 pages.

VisionPRO TH8000 Series Installation Guide, Honeywell International, Inc., Jan. 2012, 12 pages.

VisionPRO TH8000 Series Operating Manual, Honeywell International, Inc., Mar. 2011, 96 pages.

VisionPRO Wi-Fi Programmable Thermostat, Honeywell International, Inc. Operating Manual, Aug. 2012, 48 pages.

Want to Prevent Over Pressure Buildup in Your HVAC System? [online] Smarthome, 2004 [Retrieved on Sep. 30, 2004] Retrieved from the Internet: <URL: <http://www.smarthome.com/3072.html>> 1 page.

(56)

References Cited

OTHER PUBLICATIONS

White Rodgers (Emerson) Model 1F81-261 Installation and Operating Instructions, White Rodgers, Apr. 15, 2010, 8 pages.
White Rodgers (Emerson) Model 1F98EZ-1621 Homeowner's User Guide, White Rodgers, Jan. 25, 2012, 28 pages.
Arens et al., "Demand Response Enabling Technology Development", Phase I Report: Jun. 2003-Nov. 2005, Jul. 27, P:/DemandRes/UC Papers/DR-PhaseIReport-Final DraftApril24-26.doc, University of California Berkeley, pp. 1-108.
Arens et al., "New Thermostat Demand Response Enabling Technology", Poster, University of California Berkeley, Jun. 10, 2004.
Bourke, "Server Load Balancing", O'Reilly & Associates, Inc., Aug. 2001, 182 pages.
Bryant, SYSTXBUID01 Evolution Control Installation Instructions, Feb. 2004, 12 pages.
White et al., "A Conceptual Model for Simulation Load Balancing", Proc. 1998 Spring Simulation Interoperability Workshop, 1998, 7 pages.
International Search Report from PCT/US2007/008322 dated Feb. 13, 2009, 4 pages.

Notice of Allowance dated Oct. 11, 2006 from U.S. Appl. No. 10/959,361.
Notice of Allowance dated Oct. 11, 2006 from U.S. Appl. No. 10/959,362.
Notice of Allowance dated Oct. 26, 2006 from U.S. Appl. No. 10/959,494.
Notice of Allowance dated Oct. 3, 2008 from U.S. Appl. No. 11/613,090.
Notice of Allowance dated Oct. 9, 2008 from U.S. Appl. No. 11/613,116.
Office Action dated Apr. 22, 2008 from U.S. Appl. No. 11/613,090.
Office Action dated Apr. 23, 2008 from U.S. Appl. No. 11/613,116.
Office Action dated Apr. 27, 2006 from U.S. Appl. No. 10/959,494.
Office Action dated Feb. 1, 2008 from U.S. Appl. No. 11/613,110.
Office Action dated Jan. 16, 2008 from U.S. Appl. No. 11/613,116.
Office Action dated Jul. 22, 2008 from U.S. Appl. No. 11/613,110.
Office Action dated Mar. 3, 2008 from U.S. Appl. No. 11/613,090.
Office Action dated May 31, 2006 from U.S. Appl. No. 10/959,361.
Office Action dated May 31, 2006 from U.S. Appl. No. 10/959,362.
Office Action dated Nov. 15, 2007 from U.S. Appl. No. 11/613,110.

* cited by examiner




FIG. 1




FIG. 2 (PRIOR ART)






FIG. 3A

FIG. 3B








FIG. 6




FIG. 7A




FIG. 7B





FIG. 8






FIG. 10




FIG. 11








FIG. 12

**FIG. 13**

**FIG. 14**

**FIG. 15**

**FIG. 16**




FIG. 17




FIG. 18




FIG. 19

1

ELECTRONICALLY-CONTROLLED REGISTER VENT FOR ZONE HEATING AND COOLING

CROSS-REFERENCES TO RELATED APPLICATIONS

This application is a continuation of U.S. Ser. No. 11/669, 066, filed Oct. 11, 2007, which is a continuation-in-part application of U.S. Ser. No. 10/959,362, filed Oct. 6, 2004, now U.S. Pat. No. 7,168,627, the entire contents of which are hereby incorporated by reference.

BACKGROUND

1. Field of the Invention

The present invention relates to a system and method for directing heating and cooling air from an air handler to various zones in a home or commercial structure.

2. Description of the Related Art

Most traditional home heating and cooling systems have one centrally-located thermostat that controls the temperature of the entire house. The thermostat turns the Heating, Ventilating, and Air-Conditioner (HVAC) system on or off for the entire house. The only way the occupants can control the amount of HVAC air to each room is to manually open and close the register vents throughout the house.

Zoned HVAC systems are common in commercial structures, and zoned systems have been making inroads into the home market. In a zoned system, sensors in each room or group of rooms, or zones, monitor the temperature. The sensors can detect where and when heated or cooled air is needed. The sensors send information to a central controller that activates the zoning system, adjusting motorized dampers in the ductwork and sending conditioned air only to the zone in which it is needed. A zoned system adapts to changing conditions in one area without affecting other areas. For example, many two-story houses are zoned by floor. Because heat rises, the second floor usually requires more cooling in the summer and less heating in the winter than the first floor. A non-zoned system cannot completely accommodate this seasonal variation. Zoning, however, can reduce the wide variations in temperature between floors by supplying heating or cooling only to the space that needs it.

A zoned system allows more control over the indoor environment because the occupants can decide which areas to heat or cool and when. With a zoned system, the occupants can program each specific zone to be active or inactive depending on their needs. For example, the occupants can set the bedrooms to be inactive during the day while the kitchen and living areas are active.

A properly zoned system can be up to 30 percent more efficient than a non-zoned system. A zoned system supplies warm or cool air only to those areas that require it. Thus, less energy is wasted heating and cooling spaces that are not being used.

In addition, a zoned system can sometimes allow the installation of smaller capacity equipment without compromising comfort. This reduces energy consumption by reducing wasted capacity.

Unfortunately, the equipment currently used in a zoned system is relatively expensive. Moreover, installing a zoned HVAC system, or retrofitting an existing system, is far beyond the capabilities of most homeowners. Unless the homeowner has specialized training, it is necessary to hire a specially-trained professional HVAC technician to configure and install the system. This makes zoned HVAC systems expensive to

2

purchase and install. The cost of installation is such that even though the zoned system is more efficient, the payback period on such systems is many years. Such expense has severely limited the growth of zoned HVAC systems in the general home market.

SUMMARY OF THE INVENTION

The system and method disclosed herein solves these and other problems by providing an Electronically-Controlled Register vent (ECRV) that can be easily installed by a homeowner or general handyman. The ECRV can be used to convert a non-zoned HVAC system into a zoned system. The ECRV can also be used in connection with a conventional zoned HVAC system to provide additional control and additional zones not provided by the conventional zoned HVAC system. In one embodiment, the ECRV is configured have a size and form-factor that conforms to a standard manually-controlled register vent. The ECRV can be installed in place of a conventional manually-controlled register vent—often without the use of tools.

In one embodiment, the ECRV is a self-contained zoned system unit that includes a register vent, a power supply, a thermostat, and a motor to open and close the register vent. To create a zoned HVAC system, the homeowner can simply remove the existing register vents in one or more rooms and replace the register vents with the ECRVs. The occupants can set the thermostat on the EVCR to control the temperature of the area or room containing the ECRV. In one embodiment, the ECRV includes a display that shows the programmed setpoint temperature. In one embodiment, the ECRV includes a display that shows the current setpoint temperature. In one embodiment, the ECRV includes a remote control interface to allow the occupants to control the ECRV by using a remote control. In one embodiment, the remote control includes a display that shows the programmed temperature and the current temperature. In one embodiment, the remote control shows the battery status of the ECRV.

In one embodiment, the EVCR includes a pressure sensor to measure the pressure of the air in the ventilation duct that supplies air to the EVCR. In one embodiment, the EVCR opens the register vent if the air pressure in the duct exceeds a specified value. In one embodiment, the pressure sensor is configured as a differential pressure sensor that measures the difference between the pressure in the duct and the pressure in the room.

In one embodiment, the ECRV is powered by an internal battery. A battery-low indicator on the ECRV informs the homeowner when the battery needs replacement. In one embodiment, one or more solar cells are provided to recharge the batteries when light is available. In one embodiment, the register vent include a fan to draw additional air from the supply duct in order to compensate for undersized vents or zones that need additional heating or cooling air.

In one embodiment, one or more ECRVs in a zone communicate with a zone thermostat. The zone thermostat measures the temperature of the zone for all of the ECRVs that control the zone. In one embodiment, the ECRVs and the zone thermostat communicate by wireless communication methods, such as, for example, infrared communication, radio-frequency communication, ultrasonic communication, etc. In one embodiment, the ECRVs and the zone thermostat communicate by direct wire connections. In one embodiment, the ECRVs and the zone thermostat communicate using power-line communication.

In one embodiment, one or more zone thermostats communicate with a central controller.

In one embodiment, the EVCR and/or the zoned thermostat includes an occupant sensor, such as, for example, an infrared sensor, motion sensor, ultrasonic sensor, etc. The occupants can program the EVCR or the zoned thermostat to bring the zone to different temperatures when the zone is occupied and when the zone is empty. In one embodiment, the occupants can program the EVCR or the zoned thermostat to bring the zone to different temperatures depending on the time of day, the time of year, the type of room (e.g. bedroom, kitchen, etc.), and/or whether the room is occupied or empty. In one embodiment, various EVCRs and/or zoned thermostats thought a composite zone (e.g., a group of zones such as an entire house, an entire floor, one entire wing, etc.) intercommunicate and change the temperature setpoints according to whether the composite zone is empty or occupied.

In one embodiment, the home occupants can provide a priority schedule for the zones based on whether the zones are occupied, the time of day, the time of year, etc. Thus, for example, if zone corresponds to a bedroom and zone corresponds to a living room, zone can be given a relatively lower priority during the day and a relatively higher priority during the night. As a second example, if zone corresponds to a first floor, and zone corresponds to a second floor, then zone can be given a higher priority in summer (since upper floors tend to be harder to cool) and a lower priority in winter (since lower floors tend to be harder to heat). In one embodiment, the occupants can specify a weighted priority between the various zones.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a home with zoned heating and cooling.

FIG. 2 shows one example of a conventional manually-controlled register vent.

FIG. 3A is a front view of one embodiment of an electronically-controlled register vent.

FIG. 3B is a rear view of the electronically-controlled register vent shown in FIG. 3A.

FIG. 4 is a block diagram of a self-contained ECRV.

FIG. 5 is a block diagram of a self-contained ECRV with a remote control.

FIG. 6 is a block diagram of a locally-controlled zoned heating and cooling system wherein a zone thermostat controls one or more ECRVs.

FIG. 7A is a block diagram of a centrally-controlled zoned heating and cooling system wherein the central control system communicates with one or more zone thermostats and one or more ECRVs independently of the HVAC system.

FIG. 7B is a block diagram of a centrally-controlled zoned heating and cooling system wherein the central control system communicates with one or more zone thermostats and the zone thermostats communicate with one or more ECRVs.

FIG. 8 is a block diagram of a centrally-controlled zoned heating and cooling system wherein a central control system communicates with one or more zone thermostats and one or more ECRVs and controls the HVAC system.

FIG. 9 is a block diagram of an efficiency-monitoring centrally-controlled zoned heating and cooling system wherein a central control system communicates with one or more zone thermostats and one or more ECRVs and controls and monitors the HVAC system.

FIG. 10 is a block diagram of an ECRV for use in connection with the systems shown in FIGS. 6-9.

FIG. 11 is a block diagram of a basic zone thermostat for use in connection with the systems shown in FIGS. 6-9.

FIG. 12 is a block diagram of a zone thermostat with remote control for use in connection with the systems shown in FIGS. 6-9.

FIG. 13 shows one embodiment of a central monitoring system.

FIG. 14 is a flowchart showing one embodiment of an instruction loop for an ECRV or zone thermostat.

FIG. 15 is a flowchart showing one embodiment of an instruction and sensor data loop for an ECRV or zone thermostat.

FIG. 16 is a flowchart showing one embodiment of an instruction and sensor data reporting loop for an ECRV or zone thermostat.

FIG. 17 shows an ECRV configured to be used in connection with a conventional T-bar ceiling system found in many commercial structures.

FIG. 18 shows an ECRV configured to use a scrolling curtain to control airflow as an alternative to the vanes shown in FIGS. 2 and 3.

FIG. 19 is a block diagram of a control algorithm for controlling the register vents.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 shows a home 100 with zoned heating and cooling. In the home 100, an HVAC system provides heating and cooling air to a system of ducts. Sensors 101-105 monitor the temperature in various areas (zones) of the house. A zone can be a room, a floor, a group of rooms, etc. The sensors 101-105 detect where and when heating or cooling air is needed. Information from the sensors 101-105 is used to control actuators that adjust the flow of air to the various zones. The zoned system adapts to changing conditions in one area without affecting other areas. For example, many two-story houses are zoned by floor. Because heat rises, the second floor usually requires more cooling in the summer and less heating in the winter than the first floor. A non-zoned system cannot completely accommodate this seasonal variation. Zoning, however, can reduce the wide variations in temperature between floors by supplying heating or cooling only to the space that needs it.

FIG. 2 shows one example of a conventional manually-controlled register vent 200. The register 200 includes one or more vanes 201 that can be opened or closed to adjust the amount of air that flows through the register 200. Diverters 202 direct the air in a desired direction (or directions). The vanes 201 are typically provided to a mechanical mechanism so that the occupants can manipulate the vanes 201 to control the amount of air that flows out of the register 200. In some registers, the diverters 202 are fixed. In some registers, the diverters 202 are moveable to allow the occupants some control over the direction of the airflow out of the vent. Registers such as the register 200 are found throughout homes that have a central HVAC system that provides heating and cooling air. Typically, relatively small rooms such as bedrooms and bathrooms will have one or two such register vents of varying sizes. Larger rooms, such as living rooms, family rooms, etc., may have more than two such registers. The occupants of a home can control the flow of air through each of the vents by manually adjusting the vanes 201. When the register vent is located on the floor, or relatively low on the wall, such adjustment is usually not particularly difficult (unless the mechanism that controls the vanes 201 is bent or rusted). However, adjustment of the vanes 201 can be very difficult when the register vent 200 is located so high on the wall that it cannot be easily reached.

5

FIG. 3 shows one embodiment of an Electronically-Controlled Register Vent (ECRV) 300. The ECRV 300 can be used to implement a zoned heating and cooling system. The ECRV 300 can also be used as a remotely control register vent in places where the vent is located so high on the wall that is cannot be easily reached. The ECRV 300 is configured as a replacement for the vent 200. This greatly simplifies the task of retrofitting a home by replacing one or more of the register vents 200 with the ECRVs 300. In one embodiment, shown in FIG. 3, the ECRV 300 is configured to fit into approximately the same size duct opening as the conventional register vent 200. In one embodiment, the ECRV 300 is configured to fit over the duct opening used by the conventional register vent 200. In one embodiment, the ECRV 300 is configured to fit over the conventional register 200, thereby allowing the register 200 to be left in place. A control panel 301 provides one or more visual displays and, optionally, one or more user controls. A housing 302 is provided to house an actuator to control the vanes 201. In one embodiment, the housing 302 can also be used to house electronics, batteries, etc.

FIG. 4 is a block diagram of a self-contained ECRV 400, which is one embodiment of the ECRV 300 shown in FIGS. 3A and 3B and the ECRV shown in FIG. 18. In the ECRV 400, a temperature sensor 406 and a temperature sensor 416 are provided to a controller 401. The controller 401 controls an actuator system 409. In one embodiment, the actuator 409 provides position feedback to the controller 401. In one embodiment, the controller 401 reports actuator position to a central control system and/or zone thermostat. The actuator system 409 provided mechanical movements to control the airflow through the vent. In one embodiment, the actuator system 409 includes an actuator provided to the vanes 201 or other air-flow devices to control the amount of air that flows through the ECRV 400 (e.g., the amount of air that flows from the duct into the room). In one embodiment, an actuator system includes an actuator provided to one or more of the diverters 202 to control the direction of the airflow. The controller 401 also controls a visual display 403 and an optional fan 402. A user input device 408 is provided to allow the user to set the desired room temperature. An optional sensor 407 is provided to the controller 401. In one embodiment, the sensor 407 includes an air pressure and/or airflow sensor. In one embodiment, the sensor 407 includes a humidity sensor. A power source 404 provides power to the controller 401, the fan 402, the display 403, the temperature sensors 406, 416, the sensor 407, and the user input device 408 as needed. In one embodiment, the controller 401 controls the amount of power provided to the fan 402, the display 403, the sensor 406, the sensor 416, the sensor 407, and the user input device 408. In one embodiment, an optional auxiliary power source 405 is also provided to provide additional power. The auxiliary power source is a supplementary source of electrical power, such as, for example, a battery, a solar cell, an airflow (e.g., wind-powered) generator, the fan 402 acting as a generator, a nuclear-based electrical generator, a fuel cell, a thermocouple, etc.

In one embodiment, the power source 404 is based on a non-rechargeable battery and the auxiliary power source 405 includes a solar cell and a rechargeable battery. The controller 401 draws power from the auxiliary power source when possible to conserve power in the power source 404. When the auxiliary power source 405 is unable to provide sufficient power, then the controller 401 also draws power from the power source 404.

6

In an alternative embodiment, the power source 404 is configured as a rechargeable battery and the auxiliary power source 405 is configured as a solar cell that recharges the power source 404.

In one embodiment, the display 403 includes a flashing indicator (e.g., a flashing LED or LCD) when the available power from the power sources 404 and/or 405 drops below a threshold level.

The home occupants use the user input device 408 to set a desired temperature for the vicinity of the ECRV 400. The display 403 shows the setpoint temperature. In one embodiment, the display 403 also shows the current room temperature. The temperature sensor 406 measures the temperature of the air in the room, and the temperature sensor 416 measures the temperature of the air in the duct. If the room temperature is above the setpoint temperature, and the duct air temperature is below the room temperature, then the controller 401 causes the actuator 409 to open the vent. If the room temperature is below the setpoint temperature, and the duct air temperature is above the room temperature, then the controller 401 causes the actuator 409 to open the vent. Otherwise, the controller 401 causes the actuator 409 to close the vent. In other words, if the room temperature is above or below the setpoint temperature and the temperature of the air in the duct will tend to drive the room temperature towards the setpoint temperature, then the controller 401 opens the vent to allow air into the room. By contrast, if the room temperature is above or below the setpoint temperature and the temperature of the air in the duct will not tend to drive the room temperature towards the setpoint temperature, then the controller 401 closes the vent.

In one embodiment, the controller 401 is configured to provide a few degrees of hysteresis (often referred to as a thermostat deadband) around the setpoint temperature in order to avoid wasting power by excessive opening and closing of the vent.

In one embodiment, the controller 401 turns on the fan 402 to pull additional air from the duct. In one embodiment, the fan 402 is used when the room temperature is relatively far from the setpoint temperature in order to speed the movement of the room temperature towards the setpoint temperature. In one embodiment, the fan 402 is used when the room temperature is changing relatively slowly in response to the open vent. In one embodiment, the fan 402 is used when the room temperature is moving away from the setpoint and the vent is fully open. The controller 401 does not turn on or run the fan 402 unless there is sufficient power available from the power sources 404, 405. In one embodiment, the controller 401 measures the power level of the power sources 404, 405 before turning on the fan 402, and periodically (or continually) when the fan is on.

In one embodiment, the controller 401 also does not turn on the fan 402 unless it senses that there is airflow in the duct (indicating that the HVAC air-handler fan is blowing air into the duct). In one embodiment, the sensor 407 includes an airflow sensor. In one embodiment, the controller 401 uses the fan 402 as an airflow sensor by measuring (or sensing) voltage generated by the fan 402 rotating in response to air flowing from the duct through the fan and causing the fan to act as a generator. In one embodiment, the controller 401 periodically stop the fan and checks for airflow from the duct.

In one embodiment, the sensor 406 includes a pressure sensor configured to measure the air pressure in the duct. In one embodiment, the sensor 406 includes a differential pressure sensor configured to measure the pressure difference between the air in the duct and the air outside the ECRV (e.g., the air in the room). Excessive air pressure in the duct is an

indication that too many vents may be closed (thereby creating too much back pressure in the duct and reducing airflow through the HVAC system). In one embodiment, the controller 401 opens the vent when excess pressure is sensed.

The controller 401 conserves power by turning off elements of the ECRV 400 that are not in use. The controller 401 monitors power available from the power sources 404, 405. When available power drops below a low-power threshold value, the controller 401 controls the actuator 409 to an open position, activates a visual indicator using the display 403, and enters a low-power mode. In the low power mode, the controller 401 monitors the power sources 404, 405 but the controller does not provide zone control functions (e.g., the controller does not close the actuator 409). When the controller senses that sufficient power has been restored (e.g., through recharging of one or more of the power sources 404, 405, then the controller 401 resumes normal operation.

Whistling and other noises related to turbulence can be a problem when air of a certain velocity passes through an orifice or opening. In one embodiment, the controller 401 uses the physical parameters of the vent to estimate when airflow through the vent may cause undesirable noises such as whistling and the like. The controller 401 can then avoid relatively small vent openings (e.g., smaller partial openings) of the vent that produce unacceptable noises. Since whistling and other such noises are dependent on how much the vent is open and the air pressure across the vent, the openings that would cause unacceptable noises may vary depending on which other vents in the zone system are open or closed. By using data from the pressure/airflow sensor 407 and the dimensions of the vent, the controller 401 can calculate which settings are likely to produce whistling and other noises at any given time and thus, vary the allowed settings accordingly. In one embodiment, a microphone or other acoustic sensor is provided to the controller 401 such that the controller can sense acoustic noise created by air flowing through the vent. In one embodiment, the controller evaluates the amplitude of the noise detected by the acoustic sensor to determine whether unacceptable noise is being produced. In one embodiment, the controller 401 performs spectral properties of the noise (e.g., by using Fourier transform, wavelet transform, etc.) to determine whether unacceptable noise is being produced. The use of a booster fan in connection with the ECRV increases the possibility of noise. The controller 401 can also use noise estimates or measurements to help determine if a booster fan and/or the allowable speed for the fan.

If too many vents are closed off, then the remaining vents, even when completely open, may cause unacceptable noises. In one embodiment, the controller 401 informs the zone thermostats and/or control systems described below that a vent is producing noise. The zone thermostat and/or control system can then open other vents to reduce the pressure, instruct the blower fan to operate at a lower speed, turn off or reduce the speed of booster fans in the ductwork, etc.

FIG. 5 is a block diagram of a self-contained ECRV 500 with a remote control interface 501. The ECRV 500 includes the power sources 404, 405, the controller 401, the fan 402, the display 403, the temperature sensors 406, 416, the sensor 407, and the user input device 408. The remote control interface 501 is provided to the controller 401, to allow the controller 401 to communicate with a remote control 502. The controller 502 sends wireless signals to the remote control interface 501 using wireless communication such as, for example, infrared communication, ultrasonic communication, and/or radio-frequency communication.

In one embodiment, the communication is one-way, from the remote control 502 to the controller 401. The remote

control 502 can be used to set the temperature setpoint, to instruct the controller 401 to open or close the vent (either partially or fully), and/or to turn on the fan. In one embodiment, the communication between the remote control 502 and the controller 401 is two-way communication. Two-way communication allows the controller 401 to send information for display on the remote control 502, such as, for example, the current room temperature, the power status of the power sources 404, 405, diagnostic information, etc.

The ECRV 400 described in connection with FIG. 4, and the ECRV 500 described in connection with FIG. 5 are configured to operate as self-contained devices in a relatively stand-alone mode. If two ECRVs 400, 500 are placed in the same room or zone, the ECRVs 400, 500 will not necessarily operate in unison. FIG. 6 is a block diagram of a locally-controlled zoned heating and cooling system 600 wherein a zone thermostat 601 monitors the temperature of a zone 608. ECRVs 602, 603 are configured to communicate with the zone thermostat 601. One embodiment of the ECRVs 602-603 is shown, for example, in connection with FIG. 10. In one embodiment, the zone thermostat 601 sends control commands to the ECRVs 602-603 to cause the ECRVs 602-603 to open or close. In one embodiment, the zone thermostat 601 sends temperature information to the ECRVs 602-603 and the ECRVs 602-603 determine whether to open or close based on the temperature information received from the zone thermostat 601. In one embodiment, the zone thermostat 601 sends information regarding the current zone temperature and the setpoint temperature to the ECRVs 602-603.

In one embodiment, the ECRV 602 communicates with the ECRV 603 in order to improve the robustness of the communication in the system 600. Thus, for example, if the ECRV 602 is unable to communicate with the zone thermostat 601 but is able to communicate with the ECRV 603, then the ECRV 603 can act as a router between the ECRV 602 and the zone thermostat 601. In one embodiment, the ECRV 602 and the ECRV 603 communicate to arbitrate opening and closing of their respective vents.

The system 600 shown in FIG. 6 provides local control of a zone 608. Any number of independent zones can be controlled by replicating the system 600. FIG. 7A is a block diagram of a centrally-controlled zoned heating and cooling system wherein a central control system 710 communicates with one or more zone thermostats 707 708 and one or more ECRVs 702-705. In the system 700, the zone thermostat 707 measures the temperature of a zone 711, and the ECRVs 702, 703 regulate air to the zone 711. The zone thermostat 708 measures the temperature of a zone 712, and the ECRVs 704, 705 regulate air to the zone 711. A central thermostat 720 controls the HVAC system 720.

FIG. 7B is a block diagram of a centrally-controlled zoned heating and cooling system 750 that is similar to the system 700 shown in FIG. 7A. In FIG. 7B, the central system 710 communicates with the zone thermostats 707, 708, the zone thermostat 707 communicates with the ECRVs 702, 703, the zone thermostat 708 communicates with the ECRVs 704, 705, and the central system 710 communicates with the ECRVs 706, 707. In the system 750, the ECRVs 702-705 are in zones that are associated with the respective zone thermostat 707, 708 that controls the respective ECRVs 702-705. The ECRVs 706, 707 are not associated with any particular zone thermostat and are controlled directly by the central system 710. One of ordinary skill in the art will recognize that the communication topology shown in FIG. 7B can also be used in connection with the system shown in FIGS. 8 and 9.

The central system 710 controls and coordinates the operation of the zones 711 and 712, but the system 710 does not

control the HVAC system **721**. In one embodiment, the central system **710** operates independently of the thermostat **720**. In one embodiment, the thermostat **720** is provided to the central system **710** so that the central system **710** knows when the thermostat is calling for heating, cooling, or fan.

The central system **710** coordinates and prioritizes the operation of the ECRVs **702-705**. In one embodiment, the home occupants provide a priority schedule for the zones **711, 712** based on whether the zones are occupied, the time of day, the time of year, etc. Thus, for example, if zone **711** corresponds to a bedroom and zone **712** corresponds to a living room, zone **711** can be given a relatively lower priority during the day and a relatively higher priority during the night. As a second example, if zone **711** corresponds to a first floor, and zone **712** corresponds to a second floor, then zone **712** can be given a higher priority in summer (since upper floors tend to be harder to cool) and a lower priority in winter (since lower floors tend to be harder to heat). In one embodiment, the occupants can specify a weighted priority between the various zones.

Closing too many vents at one time is often a problem for central HVAC systems as it reduces airflow through the HVAC system, and thus reduces efficiency. The central system **710** can coordinate how many vents are closed (or partially closed) and thus, ensure that enough vents are open to maintain proper airflow through the system. The central system **710** can also manage airflow through the home such that upper floors receive relatively more cooling air and lower floors receive relatively more heating air.

FIG. **8** is a block diagram of a centrally-controlled zoned heating and cooling system **800**. The system **800** is similar to the system **700** and includes the zone thermostats **707, 708** to monitor the zones **711, 712**, respectively, and the ECRVs **702-705**. The zone thermostats **707, 708** and/or the ECRVs **702-705** communicate with a central controller **810**. In the system **800**, the thermostat **720** is provided to the central system **810** and the central system **810** controls the HVAC system **721** directly.

The controller **810** provides similar functionality as the controller **710**. However, since the controller **810** also controls the operation of the HVAC system **721**, the controller **810** is better able to call for heating and cooling as needed to maintain the desired temperature of the zones **711, 712**. If all, or substantially, all of the home is served by the zone thermostats and ECRVs, then the central thermostat **720** can be eliminated.

In some circumstances, depending on the return air paths in the house, the controller **810** can turn on the HVAC fan (without heating or cooling) to move air from zones that are too hot to zones that are too cool (or vice versa) without calling for heating or cooling. The controller **810** can also provide for efficient use of the HVAC system by calling for heating and cooling as needed, and delivering the heating and cooling to the proper zones in the proper amounts. If the HVAC system **721** provides multiple operating modes (e.g., high-speed, low-speed, etc.), then the controller **810** can operate the HVAC system **721** in the most efficient mode that provides the amount of heating or cooling needed.

FIG. **9** is a block diagram of an efficiency-monitoring centrally-controlled zoned heating and cooling system **900**. The system **900** is similar to the system **800**. In the system **900** the controller **810** is replaced by an efficiency-monitoring controller **910** that is configured to receive sensor data (e.g., system operating temperatures, etc.) from the HVAC system **721** to monitor the efficiency of the HVAC system **721**.

FIG. **10** is a block diagram of an ECRV **1000** for use in connection with the systems shown in FIGS. **6-9**. The ECRV

1000 includes the power sources **404, 405**, the controller **401**, the fan **402**, the display **403**, and, optionally the temperature sensors **416** and the sensor **407**, and the user input device **408**. A communication system **1081** is provided to the controller **401**. The remote control interface **501** is provided to the controller **401**, to allow the controller **401** to communicate with a remote control **502**. The controller **502** sends wireless signals to the remote control interface **501** using wireless communication such as, for example, infrared communication, ultrasonic communication, and/or radio-frequency communication.

The communication system **1081** is configured to communicate with the zone thermometer and, optionally, with the central controllers **710, 810, 910**. In one embodiment, the communication system **1081** is configured to communicate using wireless communication such as, for example, infrared communication, radio communication, or ultrasonic communication.

FIG. **11** is a block diagram of a basic zone thermostat **1100** for use in connection with the systems shown in FIGS. **6-9**. In the zone thermostat **1100**, a temperature sensor **1102** is provided to a controller **1101**. User input controls **1103** are also provided to the controller **1101** to allow the user to specify a setpoint temperature. A visual display **1110** is provided to the controller **1101**. The controller **1101** uses the visual display **1110** to show the current temperature, setpoint temperature, power status, etc. The communication system **1181** is also provided to the controller **1101**. The power source **404** and, optionally, **405** are provided to provide power for the controller **1100**, the controls **1101**, the sensor **1103**, the communication system **1181**, and the visual display **1110**.

In systems where a central controller **710, 810, 910** is used, the communication method used by the zone thermostat **1100** to communicate with the ECRV **1000** need not be the same method used by the zone thermostat **1100** to communicate with the central controller **710, 810, 910**. Thus, in one embodiment, the communication system **1181** is configured to provide one type of communication (e.g., infrared, radio, ultrasonic) with the central controller, and a different type of communication with the ECRV **1000**.

In one embodiment, the zone thermostat is battery powered. In one embodiment, the zone thermostat is configured into a standard light switch and receives electrical power from the light switch circuit.

FIG. **12** is a block diagram of a zone thermostat **1200** with remote control for use in connection with the systems shown in FIGS. **6-9**. The thermostat **1200** is similar to the thermostat **1100** and includes, the temperature sensor **1102**, the input controls **1103**, the visual display **1110**, the communication system **1181**, and the power sources **404, 405**. In the zone thermostat **1200**, the remote control interface **501** is provided to the controller **1101**.

In one embodiment, an occupant sensor **1201** is provided to the controller **1101**. The occupant sensor **1201**, such as, for example, an infrared sensor, motion sensor, ultrasonic sensor, etc. senses when the zone is occupied. The occupants can program the zone thermostat **1201** to bring the zone to different temperatures when the zone is occupied and when the zone is empty. In one embodiment, the occupants can program the zoned thermostat **1201** to bring the zone to different temperatures depending on the time of day, the time of year, the type of room (e.g. bedroom, kitchen, etc.), and/or whether the room is occupied or empty. In one embodiment, a group of zones are combined into a composite zone (e.g., a group of zones such as an entire house, an entire floor, an entire wing, etc.) and the central system **710, 810, 910** changes the tem-

11

perature setpoints of the various zones according to whether the composite zone is empty or occupied.

FIG. 13 shows one embodiment of a central monitoring station console 1300 for accessing the functions represented by the blocks 710, 810, 910 in FIGS. 7, 8, 9, respectively. The station 1300 includes a display 1301 and a keypad 1302. The occupants can specify zone temperature settings, priorities, and thermostat deadbands using the central system 1300 and/or the zone thermostats. In one embodiment, the console 1300 is implemented as a hardware device. In one embodiment, the console 1300 is implemented in software as a computer display, such as, for example, on a personal computer. In one embodiment, the zone control functions of the blocks 710, 810, 910 are provided by a computer program running on a control system processor, and the control system processor interfaces with personal computer to provide the console 1300 on the personal computer. In one embodiment, the zone control functions of the blocks 710, 810, 910 are provided by a computer program running on a control system processor provided to a hardware console 1300. In one embodiment, the occupants can use the Internet, telephone, cellular telephone, pager, etc. to remotely access the central system to control the temperature, priority, etc. of one or more zones.

FIG. 14 is a flowchart showing one embodiment of an instruction loop process 1400 for an ECRV or zone thermostat. The process 1400 begins at a power-up block 1401. After power up, the process proceeds to an initialization block 1402. After initialization, the process advances to a "listen" block 1403 wherein the ECRV or zone thermostat listens for one or more instructions. If a decision block 1404 determines that an instruction has been received, then the process advances to a "perform instruction" block 1405, otherwise the process returns to the listen block 1403.

For an ECRV, the instructions can include: open vent, close vent, open vent to a specified partially-open position, report sensor data (e.g., airflow, temperature, etc.), report status (e.g., battery status, vent position, etc.), and the like. For a zone thermostat, the instructions can include: report temperature sensor data, report temperature rate of change, report setpoint, report status, etc. In systems where the central system communicates with the ECRVs through a zone thermostat, the instructions can also include: report number of ECRVs, report ECRV data (e.g., temperature, airflow, etc.), report ECRV vent position, change ECRV vent position, etc.

In one embodiment, the listen block 1403 consumes relatively little power, thereby allowing the ECRV or zone thermostat to stay in the loop corresponding to the listen block 1403 and conditional branch 1404 for extended periods of time.

Although the listen block 1403 can be implemented to use relatively little power, a sleep block can be implemented to use even less power. FIG. 15 is a flowchart showing one embodiment of an instruction and sensor data loop process 1500 for an ECRV or zone thermostat. The process 1500 begins at a power-up block 1501. After power up, the process proceeds to an initialization block 1502. After initialization, the process advances to a "sleep" block 1503 wherein the ECRV or zone thermostat sleeps for a specified period of time. When the sleep period expires, the process advances to a wakeup block 1504 and then to a decision 1505. In the decision block 1505, if a fault is detected, then a transmit fault block 1506 is executed. The process then advances to a sensor block 1507 where sensor readings are taken. After taking sensor readings, the process advances to a listen-for-instructions block 1508. If an instruction has been received, then the process advances to a "perform instruction" block 1510; otherwise, the process returns to the sleep block 1503.

12

FIG. 16 is a flowchart showing one embodiment of an instruction and sensor data reporting loop process 1600 for an ECRV or zone thermostat. The process 1600 begins at a power-up block 1601. After power up, the process proceeds to an initialization block 1602. After initialization, the process advances to a check fault block 1603. If a fault is detected then a decision block 1604 advances the process to a transmit fault block 1605; otherwise, the process advances to a sensor block 1606 where sensor readings are taken. The data values from one or more sensors are evaluated, and if the sensor data is outside a specified range, or if a timeout period has occurred, then the process advances to a transmit data block 1608; otherwise, the process advances to a sleep block 1609. After transmitting in the transmit fault block 1605 or the transmit sensor data block 1608, the process advances to a listen block 1610 where the ECRV or zone thermostat listens for instructions. If an instruction is received, then a decision block advances the process to a perform instruction block 1612; otherwise, the process advances to the sleep block 1609. After executing the perform instruction block 1612, the process transmits an "instruction complete message" and returns to the listen block 1610.

The process flows shown in FIGS. 14-16 show different levels of interaction between devices and different levels of power conservation in the ECRV and/or zone thermostat. One of ordinary skill in the art will recognize that the ECRV and zone thermostat are configured to receive sensor data and user inputs, report the sensor data and user inputs to other devices in the zone control system, and respond to instructions from other devices in the zone control system. Thus the process flows shown in FIGS. 14-16 are provided for illustrative purposes and not by way of limitation. Other data reporting and instruction processing loops will be apparent to those of ordinary skill in the art by using the disclosure herein.

In one embodiment, the ECRV and/or zone thermostat "sleep," between sensor readings. In one embodiment, the central system 710 sends out a "wake up" signal. When an ECRV or zone thermostat receives a wake up signal, it takes one or more sensor readings, encodes it into a digital signal, and transmits the sensor data along with an identification code.

In one embodiment, the ECRV is bi-directional and configured to receive instructions from the central system. Thus, for example, the central system can instruct the ECRV to: perform additional measurements; go to a standby mode; wake up; report battery status; change wake-up interval; run self-diagnostics and report results; etc.

In one embodiment, the ECRV provides two wake-up modes, a first wake-up mode for taking measurements (and reporting such measurements if deemed necessary), and a second wake-up mode for listening for commands from the central system. The two wake-up modes, or combinations thereof, can occur at different intervals.

In one embodiment, the ECRVs use spread-spectrum techniques to communicate with the zone thermostats and/or the central system. In one embodiment, the ECRVs use frequency-hopping spread-spectrum. In one embodiment, each ECRV has an Identification code (ID) and the ECRVs attaches its ID to outgoing communication packets. In one embodiment, when receiving wireless data, each ECRV ignores data that is addressed to other ECRVs.

In one embodiment, the ECRV provides bi-directional communication and is configured to receive data and/or instructions from the central system. Thus, for example, the central system can instruct the ECRV to perform additional measurements, to go to a standby mode, to wake up, to report battery status, to change wake-up interval, to run self-diag-

13

nostics and report results, etc. In one embodiment, the ECRV reports its general health and status on a regular basis (e.g., results of self-diagnostics, battery health, etc.).

In one embodiment, the ECRV use spread-spectrum techniques to communicate with the central system. In one embodiment, the ECRV uses frequency-hopping spread-spectrum. In one embodiment, the ECRV has an address or identification (ID) code that distinguishes the ECRV from the other ECRVs. The ECRV attaches its ID to outgoing communication packets so that transmissions from the ECRV can be identified by the central system. The central system attaches the ID of the ECRV to data and/or instructions that are transmitted to the ECRV. In one embodiment, the ECRV ignores data and/or instructions that are addressed to other ECRVs.

In one embodiment, the ECRVs, zone thermostats, central system, etc., communicate on a 900 MHz frequency band. This band provides relatively good transmission through walls and other obstacles normally found in and around a building structure. In one embodiment, the ECRVs and zone thermostats communicate with the central system on bands above and/or below the 900 MHz band. In one embodiment, the ECRVs and zone thermostats listen to a radio frequency channel before transmitting on that channel or before beginning transmission. If the channel is in use, (e.g., by another device such as another central system, a cordless telephone, etc.) then the ECRVs and/or zone thermostats change to a different channel. In one embodiment, the sensor, central system coordinates frequency hopping by listening to radio frequency channels for interference and using an algorithm to select a next channel for transmission that avoids the interference. In one embodiment, the ECRV and/or zone thermostat transmits data until it receives an acknowledgement from the central system that the message has been received.

Frequency-hopping wireless systems offer the advantage of avoiding other interfering signals and avoiding collisions. Moreover, there are regulatory advantages given to systems that do not transmit continuously at one frequency. Channel-hopping transmitters change frequencies after a period of continuous transmission, or when interference is encountered. These systems may have higher transmit power and relaxed limitations on in-band spurs.

In one embodiment, the controller **401** reads the sensors **406**, **407**, **416** at regular periodic intervals. In one embodiment, the controller **401** reads the sensors **406**, **407**, **416** at random intervals. In one embodiment, the controller **401** reads the sensors **406**, **407**, **416** in response to a wake-up signal from the central system. In one embodiment, the controller **401** sleeps between sensor readings.

In one embodiment, the ECRV transmits sensor data until a handshaking-type acknowledgement is received. Thus, rather than sleep if no instructions or acknowledgements are received after transmission (e.g., after the instruction block **1510**, **1405**, **1612** and/or the transmit blocks **1605**, **1608**) the ECRV retransmits its data and waits for an acknowledgement. The ECRV continues to transmit data and wait for an acknowledgement until an acknowledgement is received. In one embodiment, the ECRV accepts an acknowledgement from a zone thermometer and it then becomes the responsibility of the zone thermometer to make sure that the data is forwarded to the central system. The two-way communication ability of the ECRV and zone thermometer provides the capability for the central system to control the operation of the ECRV and/or zone thermometer and also provides the capability for robust handshaking-type communication between the ECRV, the zone thermometer, and the central system.

In one embodiment of the system **600** shown in FIG. 6, the ECRVs **602**, **603** send duct temperature data to the zone

14

thermostat **601**. The zone thermostat **601** compares the duct temperature to the room temperature and the setpoint temperature and makes a determination as to whether the ECRVs **602**, **603** should be open or closed. The zone thermostat **601** then sends commands to the ECRVs **602**, **603** to open or close the vents. In one embodiment, the zone thermostat **601** displays the vent position on the visual display **1110**.

In one embodiment of the system **600** shown in FIG. 6, the zone thermostat **601** sends setpoint information and current room temperature information to the ECRVs **602**, **603**. The ECRVs **602**, **603** compare the duct temperature to the room temperature and the setpoint temperature and makes a determination as to whether to open or close the vents. In one embodiment, the ECRVs **602**, **603** send information to the zone thermostat **601** regarding the relative position of the vents (e.g., open, closed, partially open, etc.).

In the systems **700**, **750**, **800**, **900** (the centralized systems) the zone thermostats **707**, **708** send room temperature and setpoint temperature information to the central system. In one embodiment, the zone thermostats **707**, **708** also send temperature slope (e.g., temperature rate of rise or fall) information to the central system. In the systems where the thermostat **720** is provided to the central system or where the central system controls the HVAC system, the central system knows whether the HVAC system is providing heating or cooling; otherwise, the central system used duct temperature information provide by the ECRVs **702-705** to determine whether the HVAC system is heating or cooling. In one embodiment, ECRVs send duct temperature information to the central system. In one embodiment, the central system queries the ECRVs by sending instructions to one or more of the ECRVs **702-705** instructing the ECRV to transmit its duct temperature.

The central system determines how much to open or close ECRVs **702-705** according to the available heating and cooling capacity of the HVAC system and according to the priority of the zones and the difference between the desired temperature and actual temperature of each zone. In one embodiment, the occupants use the zone thermostat **707** to set the setpoint and priority of the zone **711**, the zone thermostat **708** to set the setpoint and priority of the zone **712**, etc. In one embodiment, the occupants use the central system console **1300** to set the setpoint and priority of each zone, and the zone thermostats to override (either on a permanent or temporary basis) the central settings. In one embodiment, the central console **1300** displays the current temperature, setpoint temperature, temperature slope, and priority of each zone.

In one embodiment, the central system allocates HVAC air to each zone according to the priority of the zone and the temperature of the zone relative to the setpoint temperature of the zone. Thus, for example, in one embodiment, the central system provides relatively more HVAC air to relatively higher priority zones that are not at their temperature setpoint than to lower priority zones or zones that are at or relatively near their setpoint temperature. In one embodiment, the central system avoids closing or partially closing too many vents in order to avoid reducing airflow in the duct below a desired minimum value.

In one embodiment, the central system monitors a temperature rate of rise (or fall) in each zone and sends commands to adjust the amount each ECRV **702-705** is open to bring higher priority zones to a desired temperature without allowing lower-priority zones to stray too far from their respective setpoint temperature.

In one embodiment, the central system uses predictive modeling to calculate an amount of vent opening for each of the ECRVs **702-705** to reduce the number of times the vents

15

are opened and closed and thereby reduce power usage by the actuators **409**. In one embodiment, the central system uses a neural network to calculate a desired vent opening for each of the ECRVs **702-705**. In one embodiment, various operating parameters such as the capacity of the central HVAC system, the volume of the house, etc., are programmed into the central system for use in calculating vent openings and closings. In one embodiment, the central system is adaptive and is configured to learn operating characteristics of the HVAC system and the ability of the HVAC system to control the temperature of the various zones as the ECRVs **702-705** are opened and closed. In an adaptive learning system, as the central system controls the ECRVs to achieve the desired temperature over a period of time, the central system learns which ECRVs need to be opened, and by how much, to achieve a desired level of heating and cooling for each zone. The use of such an adaptive central system is convenient because the installer is not required to program HVAC operating parameters into the central system. In one embodiment, the central system provides warnings when the HVAC system appears to be operating abnormally, such as, for example, when the temperature of one or more zones does not change as expected (e.g., because the HVAC system is not operating properly, a window or door is open, etc.).

In one embodiment, the adaptation and learning capability of the central system uses different adaptation results (e.g., different coefficients) based on whether the HVAC system is heating or cooling, the outside temperature, a change in the setpoint temperature or priority of the zones, etc. Thus, in one embodiment, the central system uses a first set of adaptation coefficients when the HVAC system is cooling, and a second set of adaptation coefficients when the HVAC system is heating. In one embodiment, the adaptation is based on a predictive model. In one embodiment, the adaptation is based on a neural network.

FIG. **17** shows an ECRV **1700** configured to be used in connection with a conventional T-bar ceiling system found in many commercial structures. In the ECRV **1700**, an actuator **1701** (as one embodiment of the actuator **409**) is provided to a damper **1702**. The damper **1702** is provided to a diffuser **1703** that is configured to mount in a conventional T-bar ceiling system. The ECRV **1700** can be connected to a zoned thermostat or central system by wireless or wired communication.

In one embodiment, the sensors **407** in the ECRVs include airflow and/or air velocity sensors. Data from the sensors **407** are transmitted by the ECRV to the central system. The central system uses the airflow and/or air velocity measurements to determine the relative amount of air through each ECRV. Thus, for example, by using airflow/velocity measurements, the central system can adapt to the relatively lower airflow of smaller ECRVs and ECRVs that are situated on the duct further from the HVAC blower than ECRVs which are located closer to the blower (the closer ECRVs tend to receive more airflow).

In one embodiment, the sensors **407** include humidity sensors. In one embodiment, the zone thermostat **1100** includes a zone humidity sensor provided to the controller **1101**. The zone control system (e.g., the central system, the zone thermostat, and/or ECRV) uses humidity information from the humidity sensors to calculate zone comfort values and to adjust the temperature setpoint according to a comfort value. Thus, for example, in one embodiment during a summer cooling season, the zone control system lowers the zone temperature setpoint during periods of relative high humidity, and raises the zone setpoint during periods of relatively low humidity. In one embodiment, the zone thermostat allows the

16

occupants to specify a comfort setting based on temperature and humidity. In one embodiment, the zone control system controls the HVAC system to add or remove humidity from the heating/cooling air.

FIG. **18** shows a register vent **1800** configured to use a scrolling curtain **1801** to control airflow as an alternative to the vanes shown in FIGS. **2** and **3**. An actuator **1802** (one embodiment of the actuator **409**) is provided to the curtain **1801** to move the curtain **1801** across the register to control the size of a register airflow opening. In one embodiment, the curtain **1801** is guided and held in position by a track **1803**.

In one embodiment, the actuator **1802** is a rotational actuator and the scrolling curtain **1801** is rolled around the actuator **1802**, and the register vent **1800** is open and rigid enough to be pushed into the vent opening by the actuator **1802** when the actuator **1802** rotates to unroll the curtain **1801**.

In one embodiment, the actuator **1802** is a rotational actuator and the scrolling curtain **1801** is rolled around the actuator **1802**, and the register vent **1800** is open and rigid enough to be pushed into the vent opening by the actuator **1802** when the actuator **1802** rotates to unroll the curtain **1801**. In one embodiment, the actuator **1802** is configured to

FIG. **19** is a block diagram of a control algorithm **1900** for controlling the register vents. For purposes of explanation, and not by way of limitation, the algorithm **1900** is described herein as running on the central system. However, one of ordinary skill in the art will recognize that the algorithm **1900** can be run by the central system, by the zone thermostat, by the ECRV, or the algorithm **1900** can be distributed among the central system, the zone thermostat, and the ECRV. In the algorithm **1900**, in a block **1901** of the algorithm **1900**, the setpoint temperatures from one or more zone thermostats are provided to a calculation block **1902**. The calculation block **1902** calculates the register vent settings (e.g., how much to open or close each register vent) according to the zone temperature, the zone priority, the available heating and cooling air, the previous register vent settings, etc. as described above. In one embodiment, the block **1902** uses a predictive model as described above. In one embodiment, the block **1902** calculates the register vent settings for each zone independently (e.g., without regard to interactions between zones). In one embodiment, the block **1902** calculates the register vent settings for each zone in a coupled-zone manner that includes interactions between zones. In one embodiment, the calculation block **1902** calculates new vent openings by taking into account the current vent openings and in a manner configured to minimize the power consumed by opening and closing the register vents.

Register vent settings from the block **1902** are provided to each of the register vent actuators in a block **1903**, wherein the register vents are moved to new opening positions as desired (and, optionally, one or more of the fans **402** are turned on to pull additional air from desired ducts). After setting the new vent openings in the block **1903**, the process advances to a block **1904** where new zone temperatures are obtained from the zone thermostats (the new zone temperatures being responsive to the new register vent settings made in block **1903**). The new zone temperatures are provided to an adaptation input of the block **1902** to be used in adapting a predictive model used by the block **1902**. The new zone temperatures also provided to a temperature input of the block **1902** to be used in calculating new register vent settings.

As described above, in one embodiment, the algorithm used in the calculation block **1902** is configured to predict the ECRV opening needed to bring each zone to the desired temperature based on the current temperature, the available heating and cooling, the amount of air available through each

17

ECRV, etc. The calculating block uses the prediction model to attempt to calculate the ECRV openings needed for relatively long periods of time in order to reduce the power consumed in unnecessarily by opening and closing the register vents. In one embodiment, the ECRVs are battery powered, and thus reducing the movement of the register vents extends the life of the batteries. In one embodiment, the block **1902** uses a predictive model that learns the characteristics of the HVAC system and the various zones and thus the model prediction tends to improve over time.

In one embodiment, the zone thermostats report zone temperatures to the central system and/or the ECRVs at regular intervals. In one embodiment, the zone thermostats report zone temperatures to the central system and/or the ECRVs after the zone temperature has changed by a specified amount specified by a threshold value. In one embodiment, the zone thermostats report zone temperatures to the central system and/or the ECRVs in response to a request instruction from the central system or ECRV.

In one embodiment, the zone thermostats report setpoint temperatures and zone priority values to the central system or ECRVs whenever the occupants change the setpoint temperatures or zone priority values using the user controls **1102**. In one embodiment, the zone thermostats report setpoint temperatures and zone priority values to the central system or ECRVs in response to a request instruction from the central system or ECRVs.

In one embodiment, the occupants can choose the thermostat deadband value (e.g., the hysteresis value) used by the calculation block **1902**. A relatively larger deadband value reduces the movement of the register vent at the expense of larger temperature variations in the zone.

In one embodiment, the ECRVs report sensor data (e.g., duct temperature, airflow, air velocity, power status, actuator position, etc.) to the central system and/or the zone thermostats at regular intervals. In one embodiment, the ECRVs report sensor data to the central system and/or the zone thermostats whenever the sensor data fails a threshold test (e.g., exceeds a threshold value, falls below a threshold value, falls inside a threshold range, or falls outside a threshold range, etc.). In one embodiment, the ECRVs report sensor data to the central system and/or the zone thermostats in response to a request instruction from the central system or zone thermostat.

In one embodiment, the central system is shown in FIGS. 7-9 is implemented in a distributed fashion in the zone thermostats **1100** and/or in the ECRVs. In the distributed system, the central system does not necessarily exist as a distinct device, rather, the functions of the central system can be distributed in the zone thermostats **1100** and/or the ECRVs. Thus, in a distributed system, FIGS. 7-9 represent a conceptual/computational model of the system. For example, in a distributed system, each zone thermostat **100** knows its zone priority, and the zone thermostats **1100** in the distributed system negotiate to allocate the available heating/cooling air among the zones. In one embodiment of a distributed system, one of the zone thermostats assumes the role of a master thermostat that collects data from the other zone thermostats and implements the calculation block **1902**. In one embodiment of a distributed system, the zone thermostats operate in a peer-to-peer fashion, and the calculation block **1902** is implemented in a distributed manner across a plurality of zone thermostats and/or ECRVs.

In one embodiment, the fans **402** can be used as generators to provide power to recharge the power source **404** in the ECRV. However, using the fan **402** in such a manner restricts airflow through the ECRV. In one embodiment, the controller

18

401 calculates a vent opening for the ECRV to produce the desired amount of air through the ECRV while using the fan to generate power to recharge the power source **404** (thus, in such circumstance) the controller would open the vanes more than otherwise necessary in order to compensate for the air resistance of the generator fan **402**. In one embodiment, in order to save power in the ECRV, rather than increase the vane opening, the controller **401** can use the fan as a generator. The controller **401** can direct the power generated by the fan **402** into one or both of the power sources **404**, **405**, or the controller **401** can dump the excess power from the fan into a resistive load. In one embodiment, the controller **401** makes decisions regarding vent opening versus fan usage. In one embodiment, the central system instructs the controller **401** when to use the vent opening and when to use the fan. In one embodiment, the controller **401** and central system negotiate vent opening versus fan usage.

In one embodiment, the ECRV reports its power status to the central system or zone thermostat. In one embodiment the central system or zone thermostat takes such power status into account when determining new ECRV openings. Thus, for example, if there are first and second ECRVs serving one zone and the central system knows that the first ECRV is low on power, the central system will use the second ECRV to modulate the air into the zone. If the first ECRV is able to use the fan **402** or other airflow-based generator to generate electrical power, the central system will instruct the second ECRV to a relatively closed position in and direct relatively more airflow through the first ECRV when directing air into the zone.

It will be evident to those skilled in the art that the invention is not limited to the details of the foregoing illustrated embodiments and that the present invention may be embodied in other specific forms without departing from the spirit or essential attributed thereof; furthermore, various omissions, substitutions and changes may be made without departing from the spirit of the inventions. For example, although specific embodiments are described in terms of the 900 MHz frequency band, one of ordinary skill in the art will recognize that frequency bands above and below 900 MHz can be used as well. The wireless system can be configured to operate on one or more frequency bands, such as, for example, the HF band, the VHF band, the UHF band, the Microwave band, the Millimeter wave band, etc. One of ordinary skill in the art will further recognize that techniques other than spread spectrum can also be used and/or can be used instead spread spectrum. The modulation uses is not limited to any particular modulation method, such that modulation scheme used can be, for example, frequency modulation, phase modulation, amplitude modulation, combinations thereof, etc. The one or more of the wireless communication systems described above can be replaced by wired communication. The one or more of the wireless communication systems described above can be replaced by powerline networking communication. The foregoing description of the embodiments is, therefore, to be considered in all respects as illustrative and not restrictive, with the scope of the invention being delineated by the appended claims and their equivalents.

What is claimed:

1. A system for wirelessly controlling multiple environmental zones, wherein the system comprises:

a plurality of zone controllers, wherein each of the plurality of zone controllers:

monitors a plurality of conditions associated with a zone using an associated plurality of sensors, wherein the plurality of sensors includes a temperature sensor, a humidity sensor, an occupancy sensor, and an acoustic sensor; and

19

controls a local device specific to the zone, wherein the local device includes at least one motor-driven element facilitating or inhibiting an introduction of thermal energy into the zone by differing amounts according to a position thereof; and

a central controller, wherein the central controller:

communicates, wirelessly, with the plurality of zone controllers, the central controller receiving information related to the monitored conditions for each zone as sensed by the temperature sensor, the humidity sensor, the occupancy sensor, and the acoustic sensor; and

controls the plurality of zone controllers based at least in part on the received information related to the monitored conditions for each zone.

2. The system for wirelessly controlling multiple environmental zones of claim 1, wherein the central controller:

prioritizes operation of at least two of the plurality of zone controllers.

3. The system for wirelessly controlling multiple environmental zones of claim 2, wherein operation is prioritized based at least in part on a selection from a group consisting of: whether a zone is occupied; the time of day; and the time of year.

4. The system for wirelessly controlling multiple environmental zones of claim 2, wherein operation is prioritized based at least in part on:

weighted priority between zones set by a user.

5. The system for wirelessly controlling multiple environmental zones of claim 1, wherein the central controller:

controls the plurality of zone controllers to maintain proper airflow across multiple environmental zones.

6. The system for wirelessly controlling multiple environmental zones of claim 1, wherein the central controller:

controls a fan of an HVAC system and at least one of the plurality of zone controllers to move air between zones without calling for heating and cooling from the HVAC system.

7. The system for wirelessly controlling multiple environmental zones of claim 1, wherein the local device for each zone comprises an Electronically Controlled Register Vent (ECRV).

8. The system for wirelessly controlling multiple environmental zones of claim 7, wherein the local device for each zone includes the acoustic sensor, and wherein the local device is configured to communicate data to at least one zone controller based at least in part on information from the acoustic sensor.

9. The system for wirelessly controlling multiple environmental zones of claim 1, wherein at least one of the plurality of zone controllers comprises:

a thermostat, wherein the at least one of the plurality of zone controllers is configured to control an associated local device based at least in part on data from the thermostat.

10. The system for wirelessly controlling multiple environmental zones of claim 1, wherein at least one of the plurality of zone controllers:

controls a central device associated with a plurality of zones.

11. The system for wirelessly controlling multiple environmental zones of claim 10, wherein the central device associated with the plurality of zones comprises:

an HVAC system which provides at least one of cooling or heating to the plurality of zones.

20

12. The system for wirelessly controlling multiple environmental zones of claim 1, wherein the central controller comprises:

a thermostat, wherein the central controller is configured to control at least one of the zone controllers based at least in part on data from the thermostat.

13. The system for wirelessly controlling multiple environmental zones of claim 1, wherein the central controller:

controls an HVAC system, wherein the HVAC system provides at least one of cooling or heating to a plurality of zones.

14. The system for wirelessly controlling multiple environmental zones of claim 1, wherein at least one of the plurality of zone controllers is configured to communicate at least one of the following to an associated local device:

a control command;

a zone temperature; or

a set point temperature.

15. The system for wirelessly controlling multiple environmental zones of claim 1, wherein communicating with the plurality of zone controllers comprises:

communicating bi-directionally between at least one zone controller and the central controller.

16. The system for wirelessly controlling multiple environmental zones of claim 1, wherein each of the plurality of zone controllers:

receives instructions from the central controller.

17. The system for wirelessly controlling multiple environmental zones of claim 1, wherein the central controller:

controls an HVAC system based at least in part on environmental condition data, occupancy data, and acoustic data received from at least one zone controller, wherein the HVAC system provides at least one of cooling or heating to a plurality of zones.

18. The system for wirelessly controlling multiple environmental zones of claim 1, wherein the central controller:

sends instructions to a first zone controller based at least in part on environmental condition data received from a second zone controller.

19. A method for wirelessly controlling multiple environmental zones, wherein the method comprises:

monitoring, with a plurality of zone controllers, a plurality of conditions associated with a plurality of zones using an associated plurality of sensors, wherein the plurality of sensors include a temperature sensor, a humidity sensor, an occupancy sensor, and an acoustic sensor; and

controlling, with the plurality of zone controllers, a plurality of local devices specific to each of the plurality of zones, wherein the local devices include at least one motor-driven element facilitating or inhibiting an introduction of thermal energy into the zone by differing amounts according to a position thereof;

communicating, wirelessly, between a central controller and the plurality of zone controllers, information related to the monitored conditions for each zone as sensed by the temperature sensor, the humidity sensor, the occupancy sensor, and the acoustic sensor; and

controlling, with the central controller, the plurality of zone controllers based at least in part on the information related to the monitored conditions for each zone.

20. A non-transitory computer readable medium having instructions stored thereon, the instructions being executable by one or more processors to at least:

monitor, with a plurality of zone controllers, a plurality of conditions associated with a plurality of zones using an associated plurality of sensors, wherein the plurality of

21

sensors include a temperature sensor, a humidity sensor,
an occupancy sensor, and an acoustic sensor;
control, with the plurality of zone controllers, a plurality of
local devices specific to each of the plurality of zones,
wherein the local devices include at least one motor- 5
driven element facilitating or inhibiting an introduction
of thermal energy into the zone by differing amounts
according to a position thereof;
communicate, wirelessly, between a central controller and
the plurality of zone controllers, information related to 10
the monitored conditions for each zone as sensed by the
temperature sensor, the humidity sensor, the occupancy
sensor, and the acoustic sensor; and
control, with the central controller, the plurality of zone
controllers based at least in part on the information 15
related to the monitored conditions for each zone.

* * * * *

22